BenchMix™

High Shear Lab Mixer



ADMIX

Ideal for product development and formula optimization

The BenchMix is a versatile and powerful benchtop mixer specifically designed for product development, simulation and scale up. Handling volumes from .25 to 5 gallons / 1 to 19 liters, and speeds up to 12,000 RPM, the BenchMix is ideally suited for any industry.

The BenchMix provides predictable, repeatable results from the development lab to full production when scaling up to an Admix high shear production size mixer - we back this with our process assurance warranty!

A new and improved touchscreen interface provides the option to store over 100 presets for your formulations (set parameters such as bump value, acceleration value, and RPM.) The display panel shows the amp draw, RPM and running time for the current batch.


High shear for your lab and process



This compact benchtop unit combines power, speed and versatility – features include:

- Delivers up to 2.2 kW / 3 HP
- · Variable speed from 300 12,000 RPM
- Processes 1-19 liters (.25-5 gallons)
- Easily interchange high shear or low shear mixing impellers
- · Auxiliary pumping impeller optional
- · 316SS shafting and mix heads
- · Glass bead finish stainless cabinet
- Simple operation of electronic lift
- New and improved touch screen interface





COMMITTED TO ADDING VALUE

Our customized solutions and application experience bring unparalleled value to your production process. We are results oriented, with the reputation and resources to ensure that our mixers exceed your expectations.

We encourage you to pre-test ingredients in our lab or set up an equipment trial at your own plant. Ask us for details!





BenchMix Specifications and Options

Features	OPLB-375 BenchMix	OPLB-400 BenchMix
Volume	1-19 liters (0.25-5 gallons)	1-19 liters (0.25-5 gallons)
HP	1.1 kW / 1.5 HP	2.22 kW / 3 HP
Output Speed (maximum RPM)	12,000	12,000
Adjustable Beaker Clamp (optional)	✓	✓
Low Batch Adapter (optional)	✓	✓
Scalable	✓	✓
Input Voltage	1 / 60 / 115	1 / 50-60 / 230
Max Dimensions (at extended height)	119cm x 50cm x 56cm (47"H x 20"W x 22"D)	
Mixing Impeller Options:		
Rotosolver High Shear Impeller	diameter: 29mm (1.14 in.), 40mm (1.57 in.)	
Rotostat High Shear Impeller	diameter: 24mm (0.95 in.), 50mm (1.97 in.)	
Auxiliary Pumping Impeller	diameter: 25mm (1 in.), 42mm (1.66 in.)	
Low Shear Impeller	diameter: 25mm (1 in.), 38mm (1.5 in.), 51mm (2 in.)	

